



PRODUCT NAME : 2N4037 PNP Switching Transistor (Pack of 5)

PRICE : Rs 20.00

SKU : RM2054



DESCRIPTION

WITH THE PRODUCT BY PERFORMANCE EVALUATION Copyrights by Robomart.com


Features

- Collector-Emitter Volt (V_{ce0}): 40V
- Collector-Base Volt (V_{cbo}): 60V
- Collector Current (I_c): 1.0A
- h_{fe} : 50-250 @ 150mA
- Power Dissipation (P_{tot}): 1000mW
- Current-Gain-Bandwidth (f_{total}): -
- Type: PNP


MOTOROLA
SEMICONDUCTOR TECHNICAL DATA

Order this document
 by 2N4036/D

General Purpose Transistors
PNP Silicon



2N4036
2N4037



MAXIMUM RATINGS

Rating	Symbol	2N4036	2N4037	Unit
Collector-Emitter Voltage	V_{CEO}	-65	-40	Vdc
Collector-Base Voltage	V_{CBO}	-90	-60	Vdc
Emitter-Base Voltage	V_{EBO}	-7.0	-7.0	Vdc
Base Current	I_B	-0.5		Adc
Collector Current — Continuous	I_C	-1.0		Adc
Continuous Power Dissipation at or Below $T_C = 25^\circ\text{C}$ Linear Derating Factor	P_D	5.0 28.6	5.0 28.6	Watts mW/°C
Continuous Power Dissipation at or Below $T_A = 25^\circ\text{C}$ Linear Derating Factor	P_D	1.0 5.72	1.0 5.72	Watts mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-65 to +200		°C
Lead Temperature 1/16" from Case for 10 Seconds	T_L	230		°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	2N4036	2N4037	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	35	35	°C/W

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Sustaining Voltage ⁽¹⁾ ($I_C = -100 \text{ mAdc}, I_B = 0$)	2N4036 2N4037	$V_{CEO(sus)}$	-65 -40	— —	Vdc
Collector-Base Breakdown Voltage ($I_C = -0.1 \text{ mAdc}$)	2N4037	$V_{(BR)CBO}$	-60	—	Vdc
Collector Cutoff Current ($V_{CE} = -85 \text{ Vdc}, V_{EB} = -1.5 \text{ Vdc}$) ($V_{CE} = -30 \text{ Vdc}, V_{EB} = -1.5 \text{ Vdc}, T_C = 150^\circ\text{C}$)	2N4036 2N4037	I_{CEX}	— —	-0.1 -100	mAdc
Collector Cutoff Current ($V_{CB} = -90 \text{ Vdc}, I_E = 0$) ($V_{CB} = -60 \text{ Vdc}, I_E = 0$)	2N4036 2N4037	I_{CBO}	— —	-1.0 -0.25	μAdc
Emitter Cutoff Current ($V_{EB} = -7.0 \text{ Vdc}, I_C = 0$) ($V_{EB} = -5.0 \text{ Vdc}, I_C = 0$)	2N4036 2N4037	I_{EBO}	— —	-10 -1.0	μAdc

1. Pulse Test: Pulse Width $\leq 300 \mu\text{s}$, Duty Cycle $\leq 2.0\%$.

