



PRODUCT NAME : 2N5305 NPN Darlingto
n Transistor (Pack of 5)

PRICE : Rs 20.00

SKU : RM2078



NOTE: THE PRODUCT MAY BE DIFFERENT FROM IMAGE SHOWN. Copyrights by Robomart.com

DESCRIPTION

Features

- Collector-Emitter Volt (V_{ce0}): 25V
- Collector-Base Volt (V_{cb0}): 25V
- Collector Current (I_c): 0.3A
- h_{fe} : 2,000-20,000 @ 2mA
- Power Dissipation (P_{tot}): 400mW
- Type: PNP

G E SOLID STATE

01 DE 3875081 0017947 0

7-27-27

Signal Transistors

2N5305, 6, 6A, GES5305, 6, 6A

Silicon Darlington Transistors



TO-92

TO-98

The GE/RCA 2N5305, 6, 6A and GES5305, 6, and 6A are planar, epitaxial, passivated NPN silicon Darlington transistors designed for preamplifier stages requiring input impedances of several megohms or extremely low-level, high-gain low-noise amplifier applications. These types can

be used in medium-speed switching circuits in consumer and industrial control applications.

The 2N5305, 6, and 6A are supplied in JEDEC TO-98 package, the GES5305, 6, and 6A are supplied in JEDEC TO-92 package.

Devices in TO-98 package are supplied with and without seating flange (see Dimensional Outline).

MAXIMUM RATINGS, Absolute-Maximum Values:

COLLECTOR TO EMITTER VOLTAGE (V_{CE0})	25 V
EMITTER TO BASE VOLTAGE (V_{EB0})	12 V
COLLECTOR TO BASE VOLTAGE (V_{CB0})	25 V
CONTINUOUS COLLECTOR CURRENT (I_C)	300 mA
COLLECTOR CURRENT (PULSED)* (I_C)	500 mA
CONTINUOUS BASE CURRENT (I_B)	50 mA
TOTAL POWER DISSIPATION ($T_A \leq 25^\circ\text{C}$) (P_T)	400 mW
DERATE FACTOR ($T_A > 25^\circ\text{C}$)	4 mW/ $^\circ\text{C}$
OPERATING TEMPERATURE (T_J)	-65° to +125°C
STORAGE TEMPERATURE (T_{STG})	-65° to +150°C
LEAD TEMPERATURE, $1/16" \pm 1/32"$ (1.58mm \pm 0.8mm) from case for 10s max (T_L)	+260°C

*Pulsed Conditions: Pulse width \leq 300 μs , Duty factor \leq 2%.

File Number 2065

51

G E SOLID STATE

OL DE 3875081 0017948 2

Signal Transistors

T-29-27

2N5305, 6, 6A, GES5305, 6, 6A

ELECTRICAL CHARACTERISTICS, At Ambient Temperature (T_A) = 25°C Unless Otherwise Specified

CHARACTERISTICS	SYMBOL	LIMITS		UNITS
		MIN.	MAX.	
Collector-To-Emitter Breakdown Voltage ($I_C = 10\text{ mA}, I_B = 0$)	BV_{CEO}	25	—	V
Collector-To-Base Breakdown Voltage ($I_C = 0.1\mu\text{A}, I_E = 0$)	BV_{CBO}	25	—	
Emitter-To-Base Breakdown Voltage ($I_E = 0.1\mu\text{A}, I_C = 0$)	BV_{EBO}	12	—	
DC Forward Current Transfer Ratio ($I_C = 2\text{ mA}, V_{CE} = 5\text{ V}$) 2N5305, GES5305	h_{FE}	2,000	20,000	—
($I_C = 100\text{ mA}, V_{CE} = 5\text{ V}$) 2N5305, GES5305		6,000	—	
($I_C = 2\text{ mA}, V_{CE} = 5\text{ V}$) 2N5306, GES5306A		7,000	70,000	
($I_C = 100\text{ mA}, V_{CE} = 5\text{ V}$) 2N5306, GES5306A		20,000	—	
Collector-To-Emitter Saturation Voltage ($I_C = 200\text{ mA}, I_B = 0.2\text{ mA}$)	$V_{CE(sat)}$	—	1.4	V
Base-To-Emitter Saturation Voltage ($I_C = 200\text{ mA}, I_B = 0.2\text{ mA}$)	$V_{BE(sat)}$	—	1.6	
Base-To-Emitter Voltage ($I_C = 200\text{ mA}, V_{CE} = 5\text{ V}$)	V_{BE}	—	1.5	
Collector-To-Base Cutoff Current ($V_{CB} = 25\text{ V}, I_E = 0$)	I_{CBO}	—	100	nA
($V_{CB} = 25\text{ V}, I_E = 0, T_A = 100^\circ\text{C}$)		—	20	μA
Small-Signal Current Transfer Ratio ($V_{CE} = 5\text{ V}, I_C = 2\text{ mA}, f = 1\text{ KHZ}$) 2N5305, GES5305	h_{fe}	2,000	—	—
($V_{CE} = 5\text{ V}, I_C = 2\text{ mA}, f = 1\text{ KHZ}$) 2N5306, 6A, GES5306, 6A		7,000	—	
($V_{CE} = 5\text{ V}, I_C = 2\text{ mA}, f = 10\text{ MHZ}$)		15.6	—	
Input Capacitance ($V_{EB} = 0.5\text{ V}, f = 1\text{ MHZ}$)	C_{in}	10.5 Typical		pF
Output Capacitance ($V_{CB} = 10\text{ V}, f = 1\text{ MHZ}$)	C_{out}	7.6 Typical	10	
Input Impedance ($V_{CE} = 5\text{ V}, I_C = 2\text{ mA}, f = 1\text{ KHZ}$)		850 Typical		K Ω
Gain-Bandwidth Product ($V_{CE} = 5\text{ V}, I_C = 2\text{ mA}, f = 10\text{ MHZ}$)	f_T	60	—	MHZ
Noise Figure ($V_{CE} = 5\text{ V}, I_C = 0.6\text{ mA}, R_g = 160\text{ k}\Omega$, $f = 10\text{ Hz, to } 10\text{ kHz, Bandwidth} = 15.7\text{ kHz}$) 2N5306A, GES5306A	en	195 Typical	230	nV/ $\sqrt{\text{Hz}}$

TERMINAL CONNECTIONS

TO-92 Package
 Lead 1 - Emitter
 Lead 2 - Base
 Lead 3 - Collector

TERMINAL CONNECTIONS

TO-98 Package
 Lead 1 - Emitter
 Lead 2 - Collector
 Lead 3 - Base

