



PRODUCT NAME : Wireless Charger PCB
With Coil

PRICE : Rs 759.00

SKU : RM2418



ROBOMART.COM™ ALL RIGHTS RESERVED. Copyrights by Robomart.com

DESCRIPTION

It is a wireless charger board with coil for charging Cell Phone having wireless charger module and Qi Compliant.

Specification:

- Input voltage: DC5V
- Input current: 1.2-2A
- Charging voltage: 5V
- Charging current: 500 to 1000 mA
- Charging power: 5W
- Charging distance: 7mm
- Charge efficiency: ?70%
- PCBA size: about 30 x 40mm
- Coil diameter: 25mm

Suitable for:Following phones with built-in charging receiver- can be charged directly.

- For Nokia 920/8X
- For HTC Droid DNA/Rzound/Incredible 4G LTE
- For Google (LG) Nexus 4/Nexus 5
- For LG DIL /LTE2
- For SHARP SH-13C/SH-O4D/SH-O7D/SH-02D
- Flowing phones need to buy external Qi-Standard wirless charging receiver:
- For Samsung S3 i9300 / S4 I9500
- Flowing phones need to buy external Qi-Standard wirless charging receiver jacket:
- For iPhone 4/4S
- For iPhone 5/5S

How to use:

- Please confirm that your phone is Qi-compliant.
- If there has a green indication light from the charger- the charger is working. If not- please move your phone to the center of the charger. It should commence the charging process.

- Protective cases that exceed 7 mm thick prevent the charger from working properly. In this case- remove it before charging