



PRODUCT NAME : 3" Pro Tyre BO
Motor Shaft for Arduino/Raspber
ry-Pi/Robotics

PRICE : Rs 25.00
SKU : RM0768



ROBOMART.com™ All rights reserved. Copyrights by Robomart.com

DESCRIPTION

A **wheel** is a circular component that is intended to rotate on an axial bearing. The wheel is one of the main components of the wheel and axle which is one of the six simple machines. Wheels, in conjunction with axles, allow heavy objects to be moved easily facilitating movement or transportation while supporting a load, or performing labor in machines.

A **tire** (or **tyre**) is a ring-shaped covering that fits around a wheel's rim to protect it and enable better vehicle performance. The materials of modern pneumatic tires are synthetic rubber, natural rubber, fabric and wire, along with carbon black and other chemical compounds. They consist of a tread and a body. The tread provides traction while the body provides containment for a quantity of compressed air.

Performance characteristics

- Balance

When a wheel and tire rotate, they exert a centrifugal force on the axle that depends on the location of their center of mass and the orientation of their moment of inertia.

- Rolling resistance

Rolling resistance is the resistance to rolling caused by deformation of the tire in contact with the road surface. As the tire rolls, tread enters the contact area and is deformed flat to conform to the roadway. The energy required to make the deformation depends on the inflation pressure, rotating speed, and numerous physical properties of the tire structure, such as spring force and stiffness.

Compatible Motor With the wheel:

- 150 RPM DUAL SHAFT STRAIGHT

- 150 RPM SINGLE SHAFT BO RECTANGLE
- 150 RPM SINGLE SHAFT STRAIGHT
- 300 RPM DUAL SHAFT STRAIGHT
- 50 RPM DUAL SHAFT STRAIGHT
- 75 RPM DUAL SHAFT STRAIGHT

Specifications:

- Width of the tire : 20 mm
- Diameter of the tire : 70 mm
- Diameter of the Shaft Hole : 6 mm BO type

Note : Images shown is only for representation. The actual product may vary with the picture shown